

# Glazing Services

AC Yule provides a multi-faceted glazing service which covers an extensive range of capabilities. Our team of experienced and highly trained glaziers are able to carry out a wide range of Glazing Work to meet your exacting standards.

AC Yule are an accredited FIRAS Glazing Installer. All Installers and Supervisors have been through a programme of training to ensure that they are properly equipped to undertake the installation of fire resisting glass and glazed systems.

- REPLACEMENT GLAZING
- EMERGENCY CALL-OUT GLAZING
- SHOP FRONTS AND REPLACEMENTS
- NEW BUILD GLAZING
- FIRE SCREENS, DOORS AND WINDOWS
- GLASS PARTITIONS
- BALUSTRADING
- MIRROR WARDROBE DOORS
- INSURANCE COMPANY REPAIR WORK
- SOLAR CONTROLLED & SAFETY FILMS
- TOUGHENED GLASS ASSEMBLIES
- SECONDARY GLAZING
- ROOF LIGHT GLAZING



  
**AC YULE**





AC Yule are one of Scotland's largest Glass Supply and Architectural Aluminium companies. From bases in Aberdeen, Livingston, Elgin and Sunderland a wide range of products and services are supplied including sealed units, safety glasses, fire resistant glasses, processed glass, structural glass assemblies, PVCu windows and Architectural Aluminium.

### RECOMMENDED GLAZING METHODS

At AC Yule we often get asked for recommendations on Glazing Methods and materials. To assist in ensuring your glazing is of the highest standard we as a DGU supplier would like to provide the following guidelines:

### PRIOR TO GLAZING

- Check the moisture content of the window. The moisture content should not exceed 17% as per NHBC Chapter 6.7.
- Is it low level glazing? If under 800mm from floor level safety glass must be fitted. Doors and screens under 1500mm from floor level must be fitted with safety glass.

### WET GLAZING

- Is your silicone compatible with Evostik 2895? We recommend the usage of a Low Modulus Neutral Cure with no paraffin based plasticide additives.
- Is the back check suitable for double glazing? The back check should be over 15mm deep.

At AC Yule we recommend the use of Silfix U9 Low Modulus Silicone and Flexistrip 9 x 3 Load Bearing Glazing Tape from Hodgsons.

### DRY GLAZING

For Dry Glazing we recommend the use of Sellotape 9 x 3 Dry Glaze Tape on the inner seal and 13.5 Lip Seal for outer bead. For security glazing Sellotape 9 x 3mm Security Tape should be used with 13.5 Lip Seal for outer bead. A drained bottom bead must be used in both cases.

Glazing Manuals can be provided if required, please contact the Glazing Manager, Glass & Glazing Division, Aberdeen.



AC YULE & SON LIMITED, GLASS & GLAZING DIVISION

**ABERDEEN**  
Craigshaw Road,  
West Tullos Industrial Estate,  
Aberdeen, AB12 3ZG  
Tel: 01224 230000  
Fax: 01224 230011  
Email: info@acyule.com  
Website: www.acyule.com

**LIVINGSTON**  
1 Rennie Square,  
Brucefield Industrial Park,  
Livingston,  
EH54 9DF  
Tel: 01506 423700  
Fax: 01506 423710  
Email: livingston@acyule.com

**ELGIN**  
1 Pinefield Parade,  
Pinefield Industrial Park,  
Elgin,  
IV30 6AG  
Tel: 01343 545222  
Fax: 01343 542246  
Email: elgin@acyule.com

